

ELECTRODE HOLDERS



Screw type electrode holders

TWIST 200 / 400



2004-488

Customer's benefit:

- ◆ Economical electrode holders.
- ◆ Insulation class: A.
- ◆ Well balanced, rubber handle, left hand thread.

Technical characteristics:

	TWIST 200	TWIST 400
Amperage	200 at 35%	300 at 35%
Cable Ø (mm)	25 max.	50 max.
Electrode Ø (mm)	3.2 max.	5.0 max.
Weight	335 g	480 g

TWIST 200

To order W000010565

TWIST 400

To order W000010566

VESTALETTE 250



Customer's benefit:

- ◆ Light and totally insulated, fibre glass head long life duration, left hand thread.
- ◆ Insulation class: A.

Technical characteristics:

Amperage	250 at 35%
Cable Ø (mm)	35 max.
Electrode Ø (mm)	4.0 max.
Weight	295 g

To order W000010035 W000010883*

STUBBY 400



2004-215r

Customer's benefit:

- ◆ Well known, fibre glass single part head.
- ◆ Spare parts available, right hand thread.
- ◆ Insulation class: A.

Technical characteristics:

Amperage	400 at 35%
Cable Ø (mm)	70 max.
Electrode Ø (mm)	6.3 max.
Weight	450 g

To order W000010036 W000010879*

Spare parts	To order
MASTER - Head	W000011082
STUBBY - Head	W000260716
MASTER - Insulation	W000011083
STUBBY/MASTER - Spring	W000011084
STUBBY/MASTER - Handle	W000011077
STUBBY - Body	W000011085
VESTALE - Handle	W000011086
VESTALE - Head	W000011087

Choice criteria

Screw type	Model	mm	mm ²
		Maximum	Maximum
Screw type straight	TWIST 200	3.2	25
	TWIST 400	5.0	50
	VESTALETTE 250	4.0	35
	STUBBY 400	6.3	50
	MASTER 400	8.0	95
Screw type curve	VESTALE 500	8.0	95
	CURVA 400	5.0	50
	CURVA 600	6.3	70

MASTER 500



Customer's benefit:

- ◆ Well known, fibre glass single part head.
- ◆ Spare parts available, right hand thread.
- ◆ Insulation class: A.

Technical characteristics:

Amperage	500 at 35%
Cable Ø (mm)	95 max.
Electrode Ø (mm)	8.0 max.
Weight	530 g

To order W000010037 W000010882*

VESTALE 500



Customer's benefit:

- ◆ The heavy duty electrode holder.
- ◆ High resistance.
- ◆ Fibre glass head, left hand thread.
- ◆ Insulation class: A.

Technical characteristics:

Amperage	500 at 35%
Cable Ø (mm)	95 max.
Electrode Ø (mm)	8.0 max.
Weight	470 g

To order W000010038 W000010880*

CURVA 400 / 600



2004-497

Customer's benefit:

- ◆ Curved electrode holders.
- ◆ Insulation class: B.

Technical characteristics:

	CURVA 400	CURVA 600
Amperage	400 at 35%	600 at 35%
Cable Ø (mm)	50 max.	70 max.
Electrode Ø (mm)	5.0 max.	6.3 max.
Weight	540 g	720 g

CURVA 400

To order W000010573

CURVA 600

To order W000010574

* Cat. number for display